



GSO 11913 KME Panther Pumper

Specifications

- KME Panther EMFD Five (5) Person Cab
- 10" Raised Roof
- 21" Front Bumper Extension with Center Storage Well

Drivetrain

- Cummins L9 450 HP Engine
- Allison 3000 EVS Transmission
- 20,000# Steertek Front Axle/ 26,000# Rear Axle
- Reyco Rear Suspension

Pump & Plumbing

- Waterous CSU-C20 1500 GPM Pump
- 750 Gallon UPF Poly Water Tank with Integral 20 Gallon Foam Cell
- 2.5" Rear Direct Tank Fill
- FoamPro 1600

Cab/Body

- Formed Aluminum Body
- Full Height Split Depth Compartments
- ROM Roll-up Doors, Painted Finish
- 'A' Frame Aluminum Hose Bed Cover
- Ladder, Pike Pole and Backboard Storage Beside the Water Tank on the Officer's Side of the Body
- Suction Hose Storage One (1) on Each Side of the Compartment Caps

Dimensions

- Overall Height: 122"
- Overall Length: 388"
- Wheelbase: 184"

Electrical

- Multiplex Electrical System
- Rear Camera System
- Whelen M6 and M9 Series LED NFPA Warning Light Package
- 72" FireTech HiViz LED Brow Light
- Whelen Pioneer Flood and Spotlight LED Side Scene Lights
- Whelen M9 Series LED Rear Scene Lights
- Federal Signal Q2B Pedestal Mounted on Driver's Side of Front Bumper



SAFE INDUSTRIES

5031 HWY 153 Easley, SC 29642

For More Information Call 864-845-7175

www.safeindustries.com

